



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 05.01.2021

Revision: 10.11.2020

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

None

· **1.1 Product identifier**

For Industrial, professional and consumer only

None

· **Trade name: BDX Dark Grey Primer**

· **Article number: 7119**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against** Surface Coating

· **Application of the substance / the mixture** Surface Coating

· **1.3 Details of the supplier of the safety data sheet**

· **Supplier:**

Paintman Paint Ltd.  
Unit 7 Trinity Park Industrial  
Estate,  
Sloswicke Drive,  
Retford  
Nottinghamshire  
DN22 7WQ

· **Further information obtainable from: [sales@paintman.co.uk](mailto:sales@paintman.co.uk)**

· **1.4 Emergency telephone number: +44 (0) 1777 710100 (Business hours)**

**SECTION 2: Hazards identification**

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3      H226 Flammable liquid and vapour.

STOT SE 3      H336 May cause drowsiness or dizziness.

STOT RE 1      H372 Causes damage to organs through prolonged or repeated exposure.

Aquatic Chronic 2      H411 Toxic to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02   GHS07   GHS08   GHS09

· **Signal word** Danger

· **Hazard statements**

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 05.01.2021

Revision: 10.11.2020

**Trade name: BDX Dark Grey Primer**

(Contd. of page 1)

**Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

Contains 4-isopropenyl-1-methylcyclohexane, 2-butanone oxime, cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

**2.3 Other hazards****Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**3.2 Chemical characterisation: Mixtures**

**Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

|                                                                       |                                                                                                                                                                                    |           |
|-----------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| EC number: 919-446-0<br>Reg.nr.: 01-2119458049-33-xxxx                | Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)<br>⚠ Flam. Liq. 3, H226; ⚠ STOT RE 1, H372; Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336 | >10-≤25%  |
| CAS: 7779-90-0<br>EINECS: 231-944-3<br>Reg.nr.: 01-2119485044-40-0000 | trizinc bis(orthophosphate)<br>⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410                                                                                                    | >2.5-≤10% |
| EC number: 919-857-5<br>Reg.nr.: 01-2119463258-33-xxxx                | Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics<br>⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336                                              | >2.5-≤10% |
| EC number: 918-668-5<br>Reg.nr.: 01-2119455851-35-xxxx                | Solvent naphtha (petroleum), light aromatic<br>⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336                                        | >1-≤2.5%  |
| CAS: 138-86-3<br>EINECS: 205-341-0<br>Reg.nr.: 01-2120766421-57-0000  | 4-isopropenyl-1-methylcyclohexane<br>⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 1, H410; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317                               | ≤1%       |
| CAS: 96-29-7<br>EINECS: 202-496-6<br>Reg.nr.: 01-2119539477-28        | 2-butanone oxime<br>⚠ Carc. 2, H351; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H312; Skin Sens. 1, H317                                                                                  | ≤1%       |
| CAS: 136-52-7<br>EINECS: 205-250-6<br>Reg.nr.: 01-2119524678-29       | cobalt bis(2-ethylhexanoate)<br>⚠ Repr. 1B, H360F; ⚠ Aquatic Acute 1, H400; ⚠ Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412                                      | ≤1%       |
| CAS: 22464-99-9<br>EINECS: 245-018-1<br>Reg.nr.: 01-2119979088-21     | 2-ethylhexanoic acid, zirconium salt<br>⚠ Repr. 2, H361d; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319                                                                                | ≤1%       |

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 05.01.2021

Revision: 10.11.2020

Trade name: *BDX Dark Grey Primer*

(Contd. of page 2)

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:**  
Do not induce vomiting; call for medical help immediately and show safety datasheet or label.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Prevent seepage into sewage system, workpits and cellars.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Keep receptacles tightly sealed.  
Ensure good ventilation/extraction at the workplace.  
Prevent formation of aerosols.  
Hygiene measures:  
Wash hands before breaks and at the end of workday.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 05.01.2021

Revision: 10.11.2020

**Trade name: BDX Dark Grey Primer**

(Contd. of page 3)

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risk of fires, all contaminated materials should be [stored in purpose-built containers or in metal containers with tight-fitting self-closing lids.] or [laid out flat in a single layer to dry] or [placed in a metal container soaked with water] or [washed out well with warm soapy water before disposal.] Contaminated materials should be removed from the workplace at the end of each working day and stored outside.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed and in a well-ventilated place.

Keep away from heat.

· **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics,  
<2% aromatics**

OEL Short-term value: 1200 mg/m<sup>3</sup>

**Solvent naphtha (petroleum), light aromatic**

OEL Long-term value: 100 mg/m<sup>3</sup>

**96-29-7 2-butanone oxime**

OEL Long-term value: 1 mg/m<sup>3</sup>, 0.3 ppm

**136-52-7 cobalt bis(2-ethylhexanoate)**

WEL Long-term value: 0.1 mg/m<sup>3</sup>  
as Co; Carc, Sen

· **DNELs**

**Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)**

Oral DNEL 26 mg/day (Con)

Dermal DNEL 26 mg/day (Con)

44 mg/day (Ind)

Inhalative DNEL 71 mg/m<sup>3</sup> (Con)

330 mg/m<sup>3</sup> (Ind)

**7779-90-0 trizinc bis(orthophosphate)**

Oral DNEL 0.83 mg/day (Con)

Dermal DNEL 83 mg/day (Con)

83 mg/day (Ind)

Inhalative DNEL 2.5 mg/m<sup>3</sup> (Con)

5 mg/m<sup>3</sup> (Ind)

**Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics,  
<2% aromatics**

Oral DNEL 125 mg/day (Con)

Dermal DNEL 125 mg/day (Con)

208 mg/day (Ind)

Inhalative DNEL 185 mg/m<sup>3</sup> (Con)

(Contd. on page 5)



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.01.2021

Revision: 10.11.2020

**Trade name: BDX Dark Grey Primer**

(Contd. of page 4)

|                                                    |      |                              |
|----------------------------------------------------|------|------------------------------|
|                                                    |      | 871 mg/m <sup>3</sup> (Ind)  |
| <b>Solvent naphtha (petroleum), light aromatic</b> |      |                              |
| Oral                                               | DNEL | 11 mg/day (Con)              |
| Dermal                                             | DNEL | 11 mg/day (Con)              |
|                                                    |      | 25 mg/day (Ind)              |
| Inhalative                                         | DNEL | 32 mg/m <sup>3</sup> (Con)   |
|                                                    |      | 150 mg/m <sup>3</sup> (Ind)  |
| <b>138-86-3 4-isopropenyl-1-methylcyclohexane</b>  |      |                              |
| Oral                                               | DNEL | 4.76 mg/day (Con)            |
| Dermal                                             | DNEL | 111 mg/day (Con)             |
|                                                    |      | 222 mg/day (Ind)             |
| Inhalative                                         | DNEL | 8.33 mg/m <sup>3</sup> (Con) |
|                                                    |      | 33.3 mg/m <sup>3</sup> (Ind) |
| <b>96-29-7 2-butanone oxime</b>                    |      |                              |
| Dermal                                             | DNEL | 0.78 mg/day (Con)            |
|                                                    |      | 1.3 mg/day (Ind)             |
| Inhalative                                         | DNEL | 2.7 mg/m <sup>3</sup> (Con)  |
|                                                    |      | 9 mg/m <sup>3</sup> (Ind)    |

· **PNECs**

CAS No. 1330-20-7 Xylene mixed isomers

- Fresh water; 0.327 mg/l
- Marine water; 0.327 mg/l
- Intermittent release; 0.327 mg/l
- STP; 6.58 mg/l
- Sediment (Freshwater); 12.46 mg/kg
- Sediment (Marinewater); 12.46 mg/kg
- Soil; 2.31 mg/kg

· **Additional information:** The lists valid during the making were used as basis.· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.

· **Respiratory protection:** When spraying the product, use a respiratory protective device.· **Protection of hands:**

Protective gloves

· **Eye protection:**

Tightly sealed goggles

GB

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 05.01.2021

Revision: 10.11.2020

Trade name: BDX Dark Grey Primer

(Contd. of page 5)

### SECTION 9: Physical and chemical properties

#### · 9.1 Information on basic physical and chemical properties

##### · General Information

##### · Appearance:

|                  |                 |
|------------------|-----------------|
| Form:            | Liquid          |
| Colour:          | Dark grey       |
| Odour:           | Characteristic  |
| Odour threshold: | Not determined. |

· pH-value: Not determined.

##### · Change in condition

|                                          |               |
|------------------------------------------|---------------|
| Melting point/freezing point:            | Undetermined. |
| Initial boiling point and boiling range: | 139 °C        |

· Flash point: 38 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: >200 °C

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

##### · Explosion limits:

|        |           |
|--------|-----------|
| Lower: | 0.6 Vol % |
| Upper: | 7 Vol %   |

· Vapour pressure: Not determined.

· Density at 20 °C: 1.339 g/cm<sup>3</sup>

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with water:

NOT MISCIBLE

· Partition coefficient: n-octanol/water: Not determined.

##### · Viscosity:

|                   |                 |
|-------------------|-----------------|
| Dynamic at 20 °C: | 140 mPas        |
| Kinematic:        | Not determined. |

##### · Solvent content:

Organic solvents: 32.1 %

Solids content: 67.3 %

· 9.2 Other information: No further relevant information available.

### SECTION 10: Stability and reactivity

· 10.1 Reactivity: No further relevant information available.

#### · 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions: No dangerous reactions known.

· 10.4 Conditions to avoid: No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 7)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 05.01.2021

Revision: 10.11.2020

**Trade name: BDX Dark Grey Primer**

(Contd. of page 6)

- **10.6 Hazardous decomposition products:**  
No dangerous decomposition products when stored and handled correctly

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

#### **Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)**

|            |          |                     |
|------------|----------|---------------------|
| Oral       | LD50     | >15,000 mg/kg (Rat) |
| Dermal     | LD50     | >3,400 mg/kg (Rab)  |
| Inhalative | LC50/4 h | 13.1 mg/l (Rat)     |

#### **7779-90-0 trizinc bis(orthophosphate)**

|            |          |                    |
|------------|----------|--------------------|
| Oral       | LD50     | >5,000 mg/kg (rat) |
| Inhalative | LC50/4 h | >5.7 mg/l (Rat)    |

#### **Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics**

|        |      |                    |
|--------|------|--------------------|
| Oral   | LD50 | >5,000 mg/kg (Rat) |
| Dermal | LD50 | >5,000 mg/kg (Rat) |

#### **Solvent naphtha (petroleum), light aromatic**

|            |          |                   |
|------------|----------|-------------------|
| Oral       | LD50     | 3,492 mg/kg (rat) |
| Dermal     | LD50     | 3,160 mg/kg (Rab) |
| Inhalative | LC50/4 h | >6.193 mg/l (rat) |

#### **138-86-3 4-isopropenyl-1-methylcyclohexane**

|        |      |                    |
|--------|------|--------------------|
| Oral   | LD50 | >2,000 mg/kg (Rat) |
| Dermal | LD50 | >5,000 mg/kg (Rab) |

#### **96-29-7 2-butanone oxime**

|            |          |                       |
|------------|----------|-----------------------|
| Oral       | LD50     | 2,326 mg/kg (rat)     |
| Dermal     | LD50     | 1,000 mg/kg (Rab)     |
|            |          | 200-2,000 mg/kg (rat) |
| Inhalative | LC50/4 h | >4.8 mg/l (rat)       |

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure**  
Causes damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**  
Acute Fish toxicity  
Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)  
LC50 9.22 mg/l

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 05.01.2021

Revision: 10.11.2020

**Trade name: BDX Dark Grey Primer**

(Contd. of page 7)

*Species: Oncorhynchus mykiss (rainbow trout)**Exposure duration: 96 h**Acute toxicity for daphnia**Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)**EC50 6.14 mg/l**Species: Daphnia magna (Water flea)**Exposure duration: 48 h**Acute toxicity for algae**Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)**ErC50 2.9 mg/l**Species: Pseudokirchneriella subcapitata (green algae)**Exposure duration: 72 h**Acute bacterial toxicity**Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)**EC50 1 - 10 mg/l**Ecotoxicology Assessment**Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)**Chronic aquatic toxicity: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Data based on the safety data sheet (SDS) by the supplier.*· **12.2 Persistence and degradability** No further relevant information available.· **12.3 Bioaccumulative potential** No further relevant information available.· **12.4 Mobility in soil** No further relevant information available.· **Ecotoxicological effects:**· **Remark:** Toxic for fish· **Additional ecological information:**· **General notes:***Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water**Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.**Also poisonous for fish and plankton in water bodies.**Toxic for aquatic organisms*· **12.5 Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**· **Recommendation***Must not be disposed together with household garbage. Do not allow product to reach sewage system.*· **Uncleaned packaging:**· **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

· **14.1 UN-Number**· **ADR, IMDG, IATA**

UN1263

· **14.2 UN proper shipping name**· **ADR**

1263 PAINT, ENVIRONMENTALLY HAZARDOUS

(Contd. on page 9)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.01.2021

Revision: 10.11.2020

Trade name: **BDX Dark Grey Primer**

(Contd. of page 8)

|                                                                                   |                                                                                                                  |
|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|
| · <b>IMDG</b>                                                                     | PAINT (trizinc bis(orthophosphate), DIPENTENE),                                                                  |
| · <b>IATA</b>                                                                     | MARINE POLLUTANT<br>PAINT                                                                                        |
| · <b>14.3 Transport hazard class(es)</b>                                          |                                                                                                                  |
| · <b>ADR, IMDG</b>                                                                |                                                                                                                  |
|  |                                 |
| · <b>Class</b>                                                                    | 3 Flammable liquids.                                                                                             |
| · <b>Label</b>                                                                    | 3                                                                                                                |
| · <b>IATA</b>                                                                     |                                                                                                                  |
|  |                                                                                                                  |
| · <b>Class</b>                                                                    | 3 Flammable liquids.                                                                                             |
| · <b>Label</b>                                                                    | 3                                                                                                                |
| · <b>14.4 Packing group</b>                                                       |                                                                                                                  |
| · <b>ADR, IMDG, IATA</b>                                                          | III                                                                                                              |
| · <b>14.5 Environmental hazards:</b>                                              | Product contains environmentally hazardous substances:                                                           |
| · <b>Marine pollutant:</b>                                                        | trizinc bis(orthophosphate)                                                                                      |
| · <b>Special marking (ADR):</b>                                                   | Symbol (fish and tree)                                                                                           |
| · <b>14.6 Special precautions for user</b>                                        | Warning: Flammable liquids.                                                                                      |
| · <b>Hazard identification number (Kemler code):</b>                              | 30                                                                                                               |
| · <b>EMS Number:</b>                                                              | F-E, <u>S-E</u>                                                                                                  |
| · <b>Stowage Category</b>                                                         | A                                                                                                                |
| · <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>  | Not applicable.                                                                                                  |
| · <b>Transport/Additional information:</b>                                        |                                                                                                                  |
| · <b>ADR</b>                                                                      |                                                                                                                  |
| · <b>Limited quantities (LQ)</b>                                                  | 5L                                                                                                               |
| · <b>Excepted quantities (EQ)</b>                                                 | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · <b>Transport category</b>                                                       | 3                                                                                                                |
| · <b>Tunnel restriction code</b>                                                  | D/E                                                                                                              |
| · <b>IMDG</b>                                                                     |                                                                                                                  |
| · <b>Limited quantities (LQ)</b>                                                  | 500 ml                                                                                                           |
| · <b>Excepted quantities (EQ)</b>                                                 | Code: E3<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 300 ml  |
| · <b>UN "Model Regulation":</b>                                                   | UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS                                                                 |

GB

(Contd. on page 10)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 05.01.2021

Revision: 10.11.2020

Trade name: BDX Dark Grey Primer

(Contd. of page 9)

### SECTION 15: Regulatory information

#### · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category  
E2 Hazardous to the Aquatic Environment  
P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

#### · National regulations:

#### · Technical instructions (air):

| Class | Share in % |
|-------|------------|
| I     | 0.3        |
| NK    | 32.1       |

- Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Full text of H-Statements referred to under sections 2 and 3:

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H360F May damage fertility.
- H361d Suspected of damaging the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

#### · Department issuing SDS: Product safety department: LABORATORY

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 DNEL: Derived No-Effect Level (REACH)  
 PNEC: Predicted No-Effect Concentration (REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative

(Contd. on page 11)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 05.01.2021

Revision: 10.11.2020

**Trade name: BDX Dark Grey Primer**

(Contd. of page 10)

*Flam. Liq. 3: Flammable liquids – Category 3*  
*Acute Tox. 4: Acute toxicity - dermal – Category 4*  
*Skin Irrit. 2: Skin corrosion/irritation – Category 2*  
*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*  
*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*  
*Skin Sens. 1: Skin sensitisation – Category 1*  
*Carc. 2: Carcinogenicity – Category 2*  
*Repr. 1B: Reproductive toxicity – Category 1B*  
*Repr. 2: Reproductive toxicity – Category 2*  
*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*  
*STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1*  
*Asp. Tox. 1: Aspiration hazard – Category 1*  
*Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1*  
*Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1*  
*Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*  
*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

GB