

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.01.2021 Revision: 21.10.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier For Industrial, professional and consumer only
- · Trade name: Brushing Additive A1257
- · Article number: 5651
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against Surface Coating
- · Application of the substance / the mixture

Surface Coating Surface Coating

- · 1.3 Details of the supplier of the safety data sheet
- · Supplier:

Paintman Paint Ltd.

Unit 7 Trinity Park Industrial

Estate,

Sloswicke Drive,

Retford

Nottinghamshire

DN22 7WO

- · Further information obtainable from: sales@paintman.co.uk
- · 1.4 Emergency telephone number: +44 (0) 1777 710100 (Business hours)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3

H226 Flammable liquid and vapour.

G1: 1 · 2

H315 Causes skin irritation.

Skin Irrit. 2 Skin Sens. 1

H317 May cause an allergic skin reaction.

Asp. Tox. 1

H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms









GHS02

GHS07

GHS08

GHS09

- · Signal word Danger
- · Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H304 May be fatal if swallowed and enters airways.

H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date 04.01.2021 Revision: 21.10.2020

Trade name: Brushing Additive A1257

(Contd. of page 1)

· Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 138-86-3	4-isopropenyl-1-methylcyclohexane	50-100%
EINECS: 205-341-0 Reg.nr.: 01-2120766421-57-0000	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 1, H410; ♦ Skin Irrit. 2, H315; Skin Sens. 1, H317	
EC number: 919-857-5 Reg.nr.: 01-2119463258-33-xxxx	Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	10-25%
	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336	
CAS: 22464-99-9	2-ethylhexanoic acid, zirconium salt	≤ 2.5%
EINECS: 245-018-1 Reg.nr.: 01-2119979088-21	& Repr. 2, H361d; 🕂 Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	≤ 2.5%
EINECS: 265-150-3	♠ Flam. Liq. 3, H226; ♦ Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304	
CAS: 96-29-7	2-butanone oxime	≤ 2.5%
EINECS: 202-496-6 Reg.nr.: 01-2119539477-28	♦ Carc. 2, H351; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H312; Skin Sens. 1, H317	
CAS: 136-52-7	cobalt bis(2-ethylhexanoate)	≤ 2.5%
EINECS: 205-250-6 Reg.nr.: 01-2119524678-29	 Repr. 1B, H360F; Aquatic Acute 1, H400; Eye Irrit. H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412 	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing:

Do not induce vomiting; call for medical help immediately and show safety datasheet or label.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available. (Contd. on page 3)

Printing date 04.01.2021 Revision: 21.10.2020

Trade name: Brushing Additive A1257

(Contd. of page 2)

• 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Put on breathing apparatus

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/extraction at the workplace.

Prevent formation of aerosols.

Hygiene measures:

Wash hands before breaks and at the end of workday.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risk of fires, all contaminated materials should be [stored in purpose-built containers or in metal containers with tight-fitting self-closing lids.] or [laid out flat in a single layer to dry] or [placed in a metal container soaked with water] or [washed out well with warm soapy water before disposal.] Contaminated materials should be removed from the workplace at the end of each working day and stored outside.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed and in a well-ventilated place.

Keep away from heat.

(Contd. on page 4)

Printing date 04.01.2021 Revision: 21.10.2020

Trade name: Brushing Additive A1257

(Contd. of page 3)

 \cdot 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredient	· Ingredients with limit values that require monitoring at the workplace:		
96-29-7 2-	96-29-7 2-butanone oxime		
OEL Long	g-term ν	value: 1 mg/m³, 0.3 ppm	
136-52-7 c	obalt b	is(2-ethylhexanoate)	
,	WEL Long-term value: 0.1 mg/m³		
as C	'o; Carc	, Sen	
· DNELs	· DNELs		
138-86-3	138-86-3 4-isopropenyl-1-methylcyclohexane		
Oral	DNEL	4.76 mg/day (Con)	
Dermal	DNEL	111 mg/day (Con)	
		222 mg/day (Ind)	
Inhalative	DNEL	8.33 mg/m³ (Con)	
		33.3 mg/m³ (Ind)	
•	Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics,		
	<2% aromatics		
Oral	DNEL	125 mg/day (Con)	

96-29-7 2-butanone oxime

Dermal

Dermal	DNEL	0.78 mg/day (Con)
		1.3 mg/day (Ind)
Inhalative	DNEL	1.3 mg/day (Ind) 2.7 mg/m³ (Con)
		9 mg/m^3 (Ind)

Inhalative DNEL 185 mg/m³ (Con)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

DNEL 125 mg/day (Con) 208 mg/day (Ind)

871 mg/m³ (Ind)

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- · Respiratory protection: When spraying the product, use a respiratory protective device.
- · Protection of hands:



(Contd. on page 5)


(Contd. of page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.01.2021 Revision: 21.10.2020

Trade name: Brushing Additive A1257

· Eye protection:



SECTION 9: Physical and chemic	cal properties	
9.1 Information on basic physical and ch	nemical properties	
General Information		
Appearance:		
Form:	Liquid	
Colour:	Clear	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range:	150 °C	
Flash point:	40 °C	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	245 °C	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product is not explosive. However, formation of explosive a vapour mixtures are possible.	
Explosion limits:		
Lower:	0.7 Vol %	
Upper:	6.1 Vol %	
Vapour pressure at 20 °C:	2.1 hPa	
Density at 20 °C:	0.894 g/cm³	
Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	NOT MISCIBLE	
Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic at 20 °C:	13 s (DIN 53211/4)	
Solvent content:		
Organic solvents:	60.9 %	
Solids content:	27.5 %	
9.2 Other information	No further relevant information available.	

Printing date 04.01.2021 Revision: 21.10.2020

Trade name: Brushing Additive A1257

(Contd. of page 5)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

No dangerous decomposition products when stored and handled correctly

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
138-86-3 4	138-86-3 4-isopropenyl-1-methylcyclohexane		
Oral	LD50	>2,000 mg/kg (Rat)	
Dermal	LD50	>5,000 mg/kg (Rab)	
-	Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
Oral	LD50	>5,000 mg/kg (Rat)	
Dermal	LD50	>5,000 mg/kg (Rat)	
96-29-7 2-	96-29-7 2-butanone oxime		
Oral	LD50	2,326 mg/kg (rat)	
Dermal	LD50	1,000 mg/kg (Rab)	
		200-2,000 mg/kg (rat)	
Inhalative	LC50/4 h	>4.8 mg/l (rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- $\cdot \textit{Reproductive toxicity Based on available data, the classification criteria are not met.}\\$
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

(Contd. on page 7)

Printing date 04.01.2021 Revision: 21.10.2020

Trade name: Brushing Additive A1257

(Contd. of page 6)

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- $\cdot \textbf{12.6 Other adverse effects} \ \textit{No further relevant information available}.$

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
· 14.1 UN-Number · ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name · ADR	1263 PAINT RELATED MATERIAL ENVIRONMENTALLY HAZARDOUS
· IMDG	PAINT RELATED MATERIAL (DIPENTENE), MARIN. POLLUTANT
· IATA	PAINT RELATED MATERIAL
· 14.3 Transport hazard class(es)	
· ADR, IMDG	
· Class · Label	3 Flammable liquids.
· IATA	
· Class	3 Flammable liquids.
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances 4-isopropenyl-1-methylcyclohexane
· Marine pollutant: · Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number:	Warning: Flammable liquids. 30 F-E,S- <u>E</u>

Printing date 04.01.2021 Revision: 21.10.2020

Trade name: Brushing Additive A1257

	(Contd. of page
· Stowage Category	A
· 14.7 Transport in bulk according to A	Annex II of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
\cdot ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
\cdot Excepted quantities (\widetilde{EQ})	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, II.
0	ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category
- E1 Hazardous to the Aquatic Environment
- P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Technical instructions (air):

Class	Share in %
Ι	0.2
NK	60.9

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Full text of H-Statements referred to under sections 2 and 3:
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

(Contd. on page 9)

Printing date 04.01.2021 Revision: 21.10.2020

Trade name: Brushing Additive A1257

(Contd. of page 8)

H340 May cause genetic defects.

H350 May cause cancer.

H351 Suspected of causing cancer.

H360F May damage fertility.

H361d Suspected of damaging the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· Department issuing SDS: Product safety department: LABORATORY

· Contact: Health & Safety Officer

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - dermal - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 1B: Germ cell mutagenicity - Category 1B

Carc. 1B: Carcinogenicity - Category 1B

Carc. 2: Carcinogenicity – Category 2

Repr. 1B: Reproductive toxicity – Category 1B Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

GB