

Page 1/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.01.2021 Revision: 21.10.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier For Industrial, professional and consumer only
- · Trade name: Synthetic High Opacity Undercoat White A1242
- · Article number: 6451
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against Surface Coating
- · Application of the substance / the mixture

Surface Coating Surface Coating

- $\cdot$  1.3 Details of the supplier of the safety data sheet
- · Supplier:

Paintman Paint Ltd.

Unit 7 Trinity Park Industrial

Estate,

Sloswicke Drive,

Retford

**Nottinghamshire** 

DN22 7WQ

- · Further information obtainable from: sales@paintman.co.uk
- · 1.4 Emergency telephone number: +44 (0) 1777 710100 (Business hours)

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3

H226 Flammable liquid and vapour.

Skin Sens. 1

H317 May cause an allergic skin reaction.

STOT RE 1

H372 Causes damage to organs through prolonged or repeated exposure.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms









GHS02

GHS07

GHS08 GHS09

- · Signal word Danger
- · Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 2)

Printing date 04.01.2021 Revision: 21.10.2020

Trade name: Synthetic High Opacity Undercoat White A1242

(Contd. of page 1)

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

#### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
EC number: 919-446-0 Reg.nr.: 01-2119458049-33-xxxx	Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)  ◆ Flam. Liq. 3, H226; ◆ STOT RE 1, H372; Asp. Tox. 1, H304; ◆ Aquatic Chronic 2, H411; ◆ STOT SE 3, H336	>10- <u>≤</u> 25%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33-xxxx	Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics  Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	>2.5- <i>≤</i> 10%
CAS: 138-86-3 EINECS: 205-341-0 Reg.nr.: 01-2120766421-57-0000	4-isopropenyl-1-methylcyclohexane ♠ Flam. Liq. 3, H226; ♠ Asp. Tox. 1, H304; ♠ Aquatic Chronic 1, H410; ♠ Skin Irrit. 2, H315; Skin Sens. 1, H317	>1-≤2.5%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35-XXXX	1-methoxy-2-propanol ♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	>1- <u>≤</u> 2.5%
CAS: 22464-99-9 EINECS: 245-018-1 Reg.nr.: 01-2119979088-21	2-ethylhexanoic acid, zirconium salt Repr. 2, H361d; Skin Irrit. 2, H315; Eye Irrit. 2, H319	≤1%
CAS: 96-29-7 EINECS: 202-496-6 Reg.nr.: 01-2119539477-28	2-butanone oxime ♦ Carc. 2, H351; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H312; Skin Sens. 1, H317	≤1%

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing:

Do not induce vomiting; call for medical help immediately and show safety datasheet or label.

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing date 04.01.2021 Revision: 21.10.2020

Trade name: Synthetic High Opacity Undercoat White A1242

(Contd. of page 2)

• 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/extraction at the workplace.

Prevent formation of aerosols.

Hygiene measures:

Wash hands before breaks and at the end of workday.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risk of fires, all contaminated materials should be [stored in purpose-built containers or in metal containers with tight-fitting self-closing lids.] or [laid out flat in a single layer to dry] or [placed in a metal container soaked with water] or [washed out well with warm soapy water before disposal.] Contaminated materials should be removed from the workplace at the end of each working day and stored outside.

· Information about storage in one common storage facility: Not required.

(Contd. on page 4)

Printing date 04.01.2021 Revision: 21.10.2020

Trade name: Synthetic High Opacity Undercoat White A1242

(Contd. of page 3)

- $\cdot \textit{Further information about storage conditions:}$
- Keep receptacle tightly sealed and in a well-ventilated place.

Keep away from heat.

 $\cdot$  7.3 Specific end use(s) No further relevant information available.

Aaautonai	l inform	ation about design of technical facilities: No further data; see item 7.	
8.1 Contro			
		imit values that require monitoring at the workplace:	
_		0 - C11, n-alkanes, isoalkanes, cyclics,	
<2% arom		· · · · · · · · · · · · · · · · · · ·	
		value: 1200 mg/m³	
		xy-2-propanol	
		value: 560 mg/m³, 150 ppm value: 375 mg/m³, 100 ppm	
	96-29-7 2-butanone oxime		
OEL Long	g-term v	value: 1 mg/m³, 0.3 ppm	
DNELs			
Hydrocarl		9-12, n-alkanes, isoalkanes,cyclics, aromatics (2-25%)	
Oral		26 mg/day (Con)	
Dermal	DNEL	26 mg/day (Con)	
		44 mg/day (Ind)	
Inhalative	DNEL	71 $mg/m^3$ (Con)	
		330 mg/m³ (Ind)	
Hydrocart <2% arom		9 - C11, n-alkanes, isoalkanes, cyclics,	
~2 /0 W O III			
Oral		125 mg/day (Con)	
	DNEL	125 mg/day (Con) 125 mg/day (Con)	
	DNEL	125 mg/day (Con)	
Dermal	DNEL DNEL	125 mg/day (Con) 208 mg/day (Ind)	
Dermal	DNEL DNEL	125 mg/day (Con) 208 mg/day (Ind) 185 mg/m³ (Con)	
Dermal Inhalative	DNEL DNEL DNEL	125 mg/day (Con) 208 mg/day (Ind) 185 mg/m³ (Con) 871 mg/m³ (Ind)	
Dermal Inhalative 138-86-3	DNEL DNEL DNEL 4-isopro	125 mg/day (Con) 208 mg/day (Ind) 185 mg/m³ (Con)	
Dermal Inhalative 138-86-3 4	DNEL DNEL DNEL  -isopro DNEL	125 mg/day (Con) 208 mg/day (Ind) 185 mg/m³ (Con) 871 mg/m³ (Ind) penyl-1-methylcyclohexane	
Dermal Inhalative 138-86-3 4	DNEL DNEL DNEL  -isopro DNEL	125 mg/day (Con) 208 mg/day (Ind) 185 mg/m³ (Con) 871 mg/m³ (Ind) penyl-1-methylcyclohexane 4.76 mg/day (Con)	
Dermal Inhalative 138-86-3 4 Oral Dermal	DNEL DNEL  1-isopro DNEL DNEL	125 mg/day (Con) 208 mg/day (Ind) 185 mg/m³ (Con) 871 mg/m³ (Ind) penyl-1-methylcyclohexane 4.76 mg/day (Con) 111 mg/day (Con)	
Dermal Inhalative 138-86-3 4 Oral Dermal	DNEL DNEL  1-isopro DNEL DNEL	125 mg/day (Con) 208 mg/day (Ind) 185 mg/m³ (Con) 871 mg/m³ (Ind) penyl-1-methylcyclohexane 4.76 mg/day (Con) 111 mg/day (Con) 222 mg/day (Ind)	
Dermal Inhalative 138-86-3 4 Oral Dermal Inhalative	DNEL DNEL  1-isopro DNEL DNEL DNEL DNEL	125 mg/day (Con) 208 mg/day (Ind) 185 mg/m³ (Con) 871 mg/m³ (Ind)  penyl-1-methylcyclohexane 4.76 mg/day (Con) 111 mg/day (Con) 222 mg/day (Ind) 8.33 mg/m³ (Con)	
Dermal Inhalative 138-86-3 4 Oral Dermal Inhalative	DNEL DNEL  f-isopro  DNEL  DNEL  DNEL  DNEL	125 mg/day (Con) 208 mg/day (Ind) 185 mg/m³ (Con) 871 mg/m³ (Ind) penyl-1-methylcyclohexane 4.76 mg/day (Con) 111 mg/day (Con) 222 mg/day (Ind) 8.33 mg/m³ (Con) 33.3 mg/m³ (Ind)	
Dermal Inhalative 138-86-3 4 Oral Dermal Inhalative 107-98-2 1	DNEL DNEL  f-isopro DNEL DNEL  DNEL  f-metho	125 mg/day (Con) 208 mg/day (Ind) 185 mg/m³ (Con) 871 mg/m³ (Ind) penyl-1-methylcyclohexane 4.76 mg/day (Con) 111 mg/day (Con) 222 mg/day (Ind) 8.33 mg/m³ (Con) 33.3 mg/m³ (Ind) xy-2-propanol 3.3 mg/day (Con) 18.1 mg/day (Con)	
Dermal Inhalative 138-86-3 4 Oral Dermal Inhalative 107-98-2 1 Oral Dermal	DNEL DNEL  1-isopro DNEL DNEL  DNEL  1-metho DNEL DNEL	125 mg/day (Con) 208 mg/day (Ind) 185 mg/m³ (Con) 871 mg/m³ (Ind) penyl-1-methylcyclohexane 4.76 mg/day (Con) 111 mg/day (Con) 222 mg/day (Ind) 8.33 mg/m³ (Con) 33.3 mg/m³ (Ind) xy-2-propanol 3.3 mg/day (Con) 18.1 mg/day (Con) 50.6 mg/day (Ind)	
138-86-3 4 Oral Dermal Inhalative 107-98-2 i Oral Dermal	DNEL DNEL  1-isopro DNEL DNEL  DNEL  1-metho DNEL DNEL	125 mg/day (Con) 208 mg/day (Ind) 185 mg/m³ (Con) 871 mg/m³ (Ind)  penyl-1-methylcyclohexane  4.76 mg/day (Con) 111 mg/day (Con) 222 mg/day (Ind) 8.33 mg/m³ (Con) 33.3 mg/m³ (Ind)  xy-2-propanol  3.3 mg/day (Con) 18.1 mg/day (Con) 50.6 mg/day (Ind) 43.9 mg/m³ (Con)	
Dermal Inhalative 138-86-3 4 Oral Dermal Inhalative 107-98-2 1 Oral Dermal	DNEL DNEL  J-isopro DNEL DNEL  J-metho DNEL DNEL DNEL DNEL DNEL	125 mg/day (Con) 208 mg/day (Ind) 185 mg/m³ (Con) 871 mg/m³ (Ind)  penyl-1-methylcyclohexane  4.76 mg/day (Con) 111 mg/day (Con) 222 mg/day (Ind) 8.33 mg/m³ (Con) 33.3 mg/m³ (Ind)  xy-2-propanol  3.3 mg/day (Con) 18.1 mg/day (Con) 50.6 mg/day (Ind) 43.9 mg/m³ (Con) 369 mg/m³ (Ind)	

Printing date 04.01.2021 Revision: 21.10.2020

Trade name: Synthetic High Opacity Undercoat White A1242

(Contd. of page 4)

Inhalative DNEL 2.7 mg/m³ (Con) 9 mg/m³ (Ind)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

- Respiratory protection: When spraying the product, use a respiratory protective device.
- · Protection of hands:

When skin exposure may occur, advice should be sought from the glove supplier on appropriate types and usage times for this product.



Protective gloves

· Eye protection:



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and ch	nemical properties
· General Information · Appearance:	
Form:	Liquid
Colour:	White
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	139 °C
· Flash point:	37 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	>200 °C
· Decomposition temperature:	Not determined.
$\cdot$ Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
· Explosion limits:	
Lower:	0.6 Vol %
Upper:	7 Vol %
· Vapour pressure:	Not determined.
· Density at 20 °C:	1.489 g/cm³

(Contd. on page 6)

Printing date 04.01.2021 Revision: 21.10.2020

Trade name: Synthetic High Opacity Undercoat White A1242

	(Contd. o	f page
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	NOT MISCIBLE	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic at 20 °C:	400 mPas	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	23.9 %	
Solids content:	75.8 %	
· 9.2 Other information	No further relevant information available.	

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

No dangerous decomposition products when stored and handled correctly

## SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

		vant for classification:
Hydrocarl	ons, C9-12	2, n-alkanes, isoalkanes,cyclics, aromatics (2-25%)
Oral	LD50	>15,000 mg/kg (Rat)
Dermal	<i>LD50</i>	>3,400 mg/kg (Rab)
Inhalative	LC50/4 h	13.1 mg/l (Rat)
Hydrocarl	ons, C9 - (	C11, n-alkanes, isoalkanes, cyclics,
<2% arom	atics	
Oral	LD50	>5,000 mg/kg (Rat)
Dermal	<i>LD50</i>	>5,000 mg/kg (Rat)
138-86-3 4	l-isoproper	nyl-1-methylcyclohexane
Oral	LD50	>2,000 mg/kg (Rat)
Dermal	<i>LD50</i>	>5,000 mg/kg (Rab)
107-98-2	-methoxy-	2-propanol
Oral	LD50	4,016 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (Rat)
Inhalative	LC50/4 h	25.8 mg/l (rat)
96-29-7 2-	butanone (	oxime
Oral	LD50	2,326 mg/kg (rat)
Dermal	<i>LD50</i>	1,000 mg/kg (Rab)

(Contd. on page 7)

Printing date 04.01.2021 Revision: 21.10.2020

Trade name: Synthetic High Opacity Undercoat White A1242

(Contd. of page 6)

| 200-2,000 mg/kg (rat) | Inhalative | LC50/4 h | >4.8 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure
- Causes damage to organs through prolonged or repeated exposure.
- · Aspiration hazard Based on available data, the classification criteria are not met.

#### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

#### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN-Number		
· ADR, IMDG, IATA	UN1263	
· 14.2 UN proper shipping name		
$\cdot ADR$	1263 PAINT, ENVIRONMENTALLY HAZARDOUS	
$\cdot$ IMDG	PAINT (DIPENTENE), MARINE POLLUTANT	
$\cdot$ IATA	PAINT	

(Contd. on page 8)

Printing date 04.01.2021 Revision: 21.10.2020

Trade name: Synthetic High Opacity Undercoat White A1242

(Contd. of page 7) · 14.3 Transport hazard class(es) · ADR, IMDG · Class 3 Flammable liquids. · Label  $\cdot$  IATA · Class 3 Flammable liquids. · Label 3 · 14.4 Packing group Ш · ADR, IMDG, IATA Product contains environmentally hazardous substances: · 14.5 Environmental hazards: 4-isopropenyl-1-methylcyclohexane · Marine pollutant: Symbol (fish and tree) · Special marking (ADR): Symbol (fish and tree) Warning: Flammable liquids. · 14.6 Special precautions for user · Hazard identification number (Kemler code): 30 · EMS Number: F-E,S-E· Stowage Category · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information:  $\cdot ADR$ · Limited quantities (LQ) 5LCode: E1 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · Transport category · Tunnel restriction code D/E · Limited quantities (LQ) 5L · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · UN "Model Regulation": UN 1263 PAINT, 3, III, ENVIRONMENTALLY **HAZARDOUS** 

#### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

(Contd. on page 9)

Printing date 04.01.2021 Revision: 21.10.2020

Trade name: Synthetic High Opacity Undercoat White A1242

(Contd. of page 8)

· Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Technical instructions (air):

Class	Share in %
I	0.2
NK	23.9

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Full text of H-Statements referred to under sections 2 and 3:
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H361d Suspected of damaging the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- · Department issuing SDS: Product safety department: LABORATORY
- · Contact: Health & Safety Officer
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - dermal – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity - Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. on page 10)

Page 10/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.01.2021 Revision: 21.10.2020

Trade name: Synthetic High Opacity Undercoat White A1242

(Contd. of page 9)

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2