

Page 1/9

Safety data sheet according to UK REACH

Printing date 08.07.2025

Version number: 1.03

Revision: 08.07.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier For industrial, professional & consumer use.
- · Trade name: Light Grey Synthetic Primer
- · UFI: 8H27-20JE-G000-U7JW
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against Surface Coating
- Application of the substance / the mixture Surface Coating
- \cdot 1.3 Details of the supplier of the safety data sheet
- · Supplier:

 PAINTMAN PAINT LTD Unit 7 Trinity Park Industrial Estate, Sloswicke Drive, Retford DN22 7WQ UNITED KINGDOM TEL: +44 (0)1777 710100 EMAIL: sales@paintman.co.uk

- · Further information obtainable from: www.paintman.co.uk
- · 1.4 Emergency telephone number: +44 (0)1777 710100 (business hours)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3	H226 Flammable liquid and vapour.
--------------	-----------------------------------

- Skin Sens. 1 H317 May cause an allergic skin reaction.
- STOT SE 3 H336 May cause drowsiness or dizziness.
- STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.
- · Hazard pictograms



· Signal word Danger

• *Hazard-determining components of labelling: Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) cobalt bis(2-ethylhexanoate)*

· Hazard statements

- H226 Flammable liquid and vapour.
- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

ictoraing to OK REACT

Printing date 08.07.2025

Version number: 1.03

Revision: 08.07.2025

Trade name: Light Grey Synthetic Primer

	(Contd. of page 1)
H411 Toxic to aqu	atic life with long lasting effects.	
· Precautionary stat	tements	
P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition smoking.	n sources. No
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.	
P260	Do not breathe dust/fume/gas/mist/vapours/spray.	
P303+P361+P353	3 IF ON SKIN (or hair): Take off immediately all contaminated clothing. R. water [or shower].	inse skin with
P405	Store locked up.	
P501	Dispose of contents/container in accordance with local/regional/national, regulations.	/international
· 2.3 Other hazards		
· Results of PBT an	d vPvB assessment	

· **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
EC number: 919-446-0 Reg.nr.: 01-2119458049-33-xxxx	Hydrocarbons, C9-12, n-alkanes, isoalkanes,cyclics, aromatics (2-25%) Flam. Liq. 3, H226 STOT RE 1, H372; Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336	>25- <u><</u> 50%
CAS: 7779-90-0 EINECS: 231-944-3	trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	>2.5-≤10%
Reg.nr.: 01-2119485044-40-0000 CAS: 97952-68-6	Quaternary ammonium compounds,benzylbis(hydrogenated	>1-<2.5%
EC number: 308-361-9	tallow alkyl)methyl,salts with montmorillonite STOT RE 2, H373	/1- <u></u> 2.570
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-2119524678-29	 cobalt bis(2-ethylhexanoate) Repr. 1A, H360Fd Aquatic Acute 1, H400 Eye Irrit. 2, H319; Skin Sens. 1A, H317 Aquatic Chronic 3, H412 	≤1%
CAS: 1314-13-2 EINECS: 215-222-5 Reg.nr.: 01-2119463881-32-xxxx	zinc oxide	≤1%
CAS: 22464-99-9 EINECS: 245-018-1 Reg.nr.: 01-2119979088-21	 2-ethylhexanoic acid, zirconium salt Repr. 2, H361d Skin Irrit. 2, H315; Eye Irrit. 2, H319 	≤1%

SECTION 4: First aid measures

• 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

• After inhalation:

Supply fresh air and call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

⁻ GB

Printing date 08.07.2025

Version number: 1.03

Revision: 08.07.2025

(Contd. of page 2)

Trade name: Light Grey Synthetic Primer

Supply fresh air; consult doctor in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing.

- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing:
- Do not induce vomiting; call for medical help immediately and show safety datasheet or label.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

<u>SECTION 5:</u> Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • For safety reasons unsuitable extinguishing agents: Water with full jet
- \cdot 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Prevent seepage into sewage system, workpits and cellars. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Keep receptacles tightly sealed.
Ensure good ventilation/extraction at the workplace.
Prevent formation of aerosols.
Hygiene measures:
Wash hands before breaks and at the end of workday.
Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

(Contd. on page 4)

GB

Version number: 1.03

Revision: 08.07.2025

Trade name: Light Grey Synthetic Primer

Printing date 08.07.2025

• Further information about storage conditions:

Keep receptacle tightly sealed and in a well-ventilated place. Keep away from heat. 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see section 7.

· Ingredients with limit values that require monitoring at the workplace:

136-52-7 cobalt bis(2-ethylhexanoate)

WEL Long-term value: 0.1 mg/m³

as Co; Carc, Sen

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately.
- Respiratory protection: When spraying the product, use a respiratory protective device.
- Protection of hands:



Protective gloves

· Eye protection:



Tightly sealed goggles

9.1 Information on basic physical a	nd chemical properties	
General Information		
Appearance:		
Form:	Liquid	
Colour:	Light grey	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling ra	unge: 155 °C	
Flash point:	40 °C	
Flammability	Flammable.	
Auto-ignition temperature:	242 °C	
Decomposition temperature:	Not determined.	

(Contd. of page 3)

GB

Printing date 08.07.2025

Version number: 1.03

Revision: 08.07.2025

Trade name: Light Grey Synthetic Primer

	(Contd. of page 4
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air, vapour mixtures are possible.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	6 Vol %
Vapour pressure:	Not determined.
Density at 20 °C:	1.471 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	NOT MISCIBLE
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic at 20 °C:	300 mPas
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	26.9 %
Water:	0.0 %
Solids content:	73.2 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable under normal conditions
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

No dangerous decomposition products when stored and handled correctly

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

- · Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- $\cdot \textit{Reproductive toxicity Based on available data, the classification criteria are not met.}$

· STOT-single exposure

May cause drowsiness or dizziness.

(Contd. on page 6)

GB -

Printing date 08.07.2025

Version number: 1.03

Revision: 08.07.2025

Trade name: Light Grey Synthetic Primer

- · STOT-repeated exposure
- Causes damage to organs through prolonged or repeated exposure.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- Remark: Toxic for fish
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number	
ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name	
ADR	1263 PAINT, ENVIRONMENTALLY HAZARDOUS
IMDG	PAINT, MARINE POLLUTANT
IATA	PAINT
14.3 Transport hazard class(es)	
ADR, IMDG	
Class	3 Flammable liquids.

(Contd. of page 5)

Printing date 08.07.2025

Version number: 1.03

Revision: 08.07.2025

Trade name: Light Grey Synthetic Primer

	(Contd. of page
· Label	3
·IATA	
3	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDĞ, IATA	III
· 14.5 Environmental hazards:	Product contains environmentally hazardous substance
	trizinc bis(orthophosphate)
· Marine pollutant:	Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Flammable liquids.
• Hazard identification number (Kemler code):	30
· EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
· Stowage Category	A
· 14.7 Transport in bulk according to Annex II of	of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
·ADR	
· Limited quantities (LQ)	5L
\cdot Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
T	Maximum net quantity per outer packaging: 1000 ml
• Transport category • Tunnel restriction code	3 D/E
· 1 unnet restriction code	
·IMDG	cr.
· Limited quantities (LQ)	5L
\cdot Excepted quantities (EQ)	Code: E1 Maximum net quantity par inner packaging, 30 ml
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
	1 11 1 0 0
· UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALL
	HAZARDOUS

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· MAK (Gern	an Maximum Workplace Concentration)	
13463-67-7	titanium dioxide	34
1333-86-4	Carbon black	31
100-41-4	ethylbenzene	34
· Poisons Act		
Regulated e	xplosives precursors	
None of the	ingredients is listed.	
Regulated p	oisons	
None of the	ingredients is listed.	
		(Contd. on page

Printing date 08.07.2025

Version number: 1.03

Revision: 08.07.2025

Trade name: Light Grey Synthetic Primer

(Contd. of page 7)

· Reportable explosives precursors

None of the ingredients is listed.


· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category E2 Hazardous to the Aquatic Environment
- P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:

· Technical instructions (air):



· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Full text of H-Statements referred to under sections 2 and 3:

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H360Fd May damage fertility. Suspected of damaging the unborn child.
- H361d Suspected of damaging the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- *H400* Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

· Department issuing SDS: Product safety department: LABORATORY

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- ATE: Acute toxicity estimate values
- Flam. Liq. 3: Flammable liquids Category 3
- Skin Irrit. 2: Skin corrosion/irritation Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

- Skin Sens. 1: Skin sensitisation Category 1
- Skin Sens. 1A: Skin sensitisation Category 1A
- *Repr. 1A: Reproductive toxicity Category 1A Repr. 2: Reproductive toxicity – Category 2*

(Contd. on page 9)

Printing date 08.07.2025

Version number: 1.03

Revision: 08.07.2025

Trade name: Light Grey Synthetic Primer

	(Contd. of page 8)
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1	
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2	
Asp. Tox. 1: Aspiration hazard – Category 1	
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1	
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1	
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2	
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
• * Data compared to the previous version altered.	
	GB