

Page 1/9

Safety data sheet according to UK REACH

Printing date 07.07.2025

Version number: 1.02

Revision: 19.06.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier For industrial, professional & consumer use.
- · Trade name: <u>Paintman Paint Brushing Additive</u>
- · UFI: 3027-10E1-N001-V62H
- 1.2 Relevant identified uses of the substance or mixture and uses advised against Surface Coating • Application of the substance / the mixture Surface Coating

 1.3 Details of the supplier of the safety data sheet Supplier: PAINTMAN PAINT LTD Unit 7 Trinity Park Industrial Estate, Sloswicke Drive, Retford DN22 7WQ UNITED KINGDOM TEL: +44 (0)1777 710100 EMAIL: sales@paintman.co.uk

- Further information obtainable from: www.paintman.co.uk
- · 1.4 Emergency telephone number: +44 (0)1777 710100 (business hours)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

•	Classification acco	ording to Regulation (EC) No 1272/2008
	Flam. Liq. 3	H226 Flammable liquid and vapour.
	Skin Irrit. 2	H315 Causes skin irritation.
	Skin Sens. 1	H317 May cause an allergic skin reaction.
	Asp. Tox. 1	H304 May be fatal if swallowed and enters airways.
	Aquatic Acute 1	H400 Very toxic to aquatic life.
	Aquatic Chronic 1	H410 Very toxic to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation. • *Hazard pictograms*



H226 Flammable liquid and vapour.

· Signal word Danger

Hazard-determining components of labelling:
 4-isopropenyl-1-methylcyclohexane
 Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics,
 <2% aromatics
 cobalt bis(2-ethylhexanoate)
 Hazard statements

(Contd. on page 2)

GB

Version number: 1.02

Revision: 19.06.2025

Trade name: Paintman Paint Brushing Additive

	(Contd. of page 1)
H315 Causes skin	irritation.
H317 May cause	an allergic skin reaction.
H304 May be fate	Il if swallowed and enters airways.
H410 Very toxic t	o aquatic life with long lasting effects.
· Precautionary sta	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P303+P361+P35	3 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with
	water [or shower].
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
\cdot 2.3 Other hazard	8
-10 0 Magara	

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

CAS: 138-86-3	4-isopropenyl-1-methylcyclohexane	>50-≤100%
EINECS: 205-341-0	🚸 Flam. Liq. 3, H226	
Reg.nr.: 01-2120766421-57-0000	🚯 Asp. Tox. 1, H304	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Irrit. 2, H315; Skin Sens. 1, H317	
EC number: 919-857-5 Reg.nr.: 01-2119463258-33-xxxx	Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	>10-≤25%
	 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 	
CAS: 22464-99-9	2-ethylhexanoic acid, zirconium salt	<i>≤l%</i>
EINECS: 245-018-1 Reg.nr.: 01-2119979088-21	 Repr. 2, H361d Skin Irrit. 2, H315; Eye Irrit. 2, H319 	
CAS: 136-52-7	cobalt bis(2-ethylhexanoate)	<i>≤1%</i>
EINECS: 205-250-6	🚸 Repr. 1A, H360Fd	
Reg.nr.: 01-2119524678-29	Aquatic Acute 1, H400	
	Eye Irrit. 2, H319; Skin Sens. 1A, H317 Aquatic Chronic 3, H412	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information: Immediately remove any clothing soiled by the product.

• After inhalation:

Supply fresh air and call for a doctor.

In case of unconsciousness place patient stably in side position for transportation. Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)

- GB

Printing date 07.07.2025

Version number: 1.02

Revision: 19.06.2025

(Contd. of page 2)

Trade name: Paintman Paint Brushing Additive

• After skin contact:

- Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing:
- Do not induce vomiting; call for medical help immediately and show safety datasheet or label.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Put on breathing apparatus

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Prevent seepage into sewage system, workpits and cellars. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep receptacles tightly sealed. Ensure good ventilation/extraction at the workplace. Prevent formation of aerosols. Hygiene measures: Wash hands before breaks and at the end of workday.

- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risk of fires, all contaminated materials should be [stored in purpose-built containers or in metal containers with tight-fitting self-closing lids.] or [laid out flat in a single layer to dry] or [placed in a metal container soaked with water] or [washed out well with warm soapy water before disposal.] Contaminated materials should be removed from the workplace at the end of each working day and stored outside.

(Contd. on page 4)

⁻ GB

Printing date 07.07.2025

Version number: 1.02

Revision: 19.06.2025

(Contd. of page 3)

Trade name: Paintman Paint Brushing Additive

- Information about storage in one common storage facility: Not required. • Further information about storage conditions:
- Keep receptacle tightly sealed and in a well-ventilated place. Keep away from heat.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Additional information about design of technical facilities: No further data; see section 7.
- · Ingredients with limit values that require monitoring at the workplace:

Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics,

<2% aromatics

OEL Short-term value: 1200 mg/m³

136-52-7 cobalt bis(2-ethylhexanoate)

WEL Long-term value: 0.1 mg/m³ as Co; Carc, Sen

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

- *Respiratory protection: When spraying the product, use a respiratory protective device.*
- Protection of hands:

M2

Protective gloves

· Eye protection:



Tightly sealed goggles

• 9.1 Information on basic physical and chemical properties • General Information		
Appearance:		
Form:	Liquid	
Colour:	Clear	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling rai	nge: 150 °C	
Flash point:	40 °C	

Printing date 07.07.2025

Version number: 1.02

Revision: 19.06.2025

Trade name: Paintman Paint Brushing Additive

	(Contd. of page 4)
· Flammability	Flammable.
· Auto-ignition temperature:	240 °C
Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
Explosion limits:	
Lower:	0.6 Vol %
Upper:	6.5 Vol %
Vapour pressure at 20 °C:	2.1 hPa
Density at 20 °C:	0.881 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	NOT MISCIBLE
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	20 s (ISO 4 mm)
Solvent content:	
Organic solvents:	72.5 %
Solids content:	27.7%
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability Stable under normal conditions
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

No dangerous decomposition products when stored and handled correctly

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

- Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:

· Skin corrosion/irritation

- Causes skin irritation.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 6)

GB

Printing date 07.07.2025

Version number: 1.02

Revision: 19.06.2025

(Contd. of page 5)

Trade name: Paintman Paint Brushing Additive

- · Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- STOT-single exposure Based on available data, the classification criteria are not met.
- $\cdot \textit{STOT-repeated exposure Based on available data, the classification criteria are not met.}$
- Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- *Remark:* Very toxic for fish
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

- Very toxic for aquatic organisms
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR	1263 PAINT RELATED MATERIAL ENVIRONMENTALLY HAZARDOUS
IMDG	PAINT RELATED MATERIAL, MARINE POLLUTANT
IATA	PAINT RELATED MATERIAL
14.3 Transport hazard class(es) ADR, IMDG	

Printing date 07.07.2025

Version number: 1.02

Revision: 19.06.2025

Trade name: Paintman Paint Brushing Additive

	(Contd. of page
Label	3
IATA	
3	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	111
14.5 Environmental hazards:	Product contains environmentally hazardous substance
	4-isopropenyl-1-methylcyclohexane
Marine pollutant: Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
· · · · · ·	,
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	<i>30</i>
EMS Number:	F-E, <u>S-E</u> A
Stowage Category	
14.7 Transport in bulk according to Annex II of	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities $(\tilde{E}Q)$	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, 11
~	ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · MAK (German Maximum Workplace Concentration)
- None of the ingredients is listed.
- · Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

(Contd. on page 8)

GB

Printing date 07.07.2025

Version number: 1.02

Revision: 19.06.2025

(Contd. of page 7)

Trade name: Paintman Paint Brushing Additive

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category


E1 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

· National regulations:

• Technical instructions (air):



· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Full text of H-Statements referred to under sections 2 and 3:

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H360Fd May damage fertility. Suspected of damaging the unborn child.
- H361d Suspected of damaging the unborn child.
- H400 Very toxic to aquatic life.
- *H410 Very toxic to aquatic life with long lasting effects.*
- *H412 Harmful to aquatic life with long lasting effects.*
- · Department issuing SDS: Product safety department: LABORATORY

· Contact: Health & Safety Officer

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- *PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative*
- ATE: Acute toxicity estimate values
- Flam. Liq. 3: Flammable liquids Category 3
- Skin Irrit. 2: Skin corrosion/irritation Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation Category 2
- Skin Sens. 1: Skin sensitisation Category 1
- Skin Sens. 1A: Skin sensitisation Category 1A
- Repr. 1A: Reproductive toxicity Category 1A
- Repr. 2: Reproductive toxicity Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) Category 3
- Asp. Tox. 1: Aspiration hazard Category 1

Printing date 07.07.2025

Version number: 1.02

Revision: 19.06.2025

(Contd. of page 8)

Trade name: Paintman Paint Brushing Additive

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 • * Data compared to the previous version altered.

GB –