

Page 1/10

Safety data sheet according to UK REACH

Printing date 08.07.2025 Version number: 1.03 Revision: 08.07.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier For industrial, professional & consumer use.
- · Trade name: Red Oxide Synthetic Primer
- · **UFI**: 4M27-K07T-S00G-GK4Y
- 1.2 Relevant identified uses of the substance or mixture and uses advised against Surface Coating
- · Application of the substance / the mixture

Surface Coating

Synthetic Anti Corrosive Primer

- · 1.3 Details of the supplier of the safety data sheet
- · Supplier:

PAINTMAN PAINT LTD

Unit 7 Trinity Park Industrial Estate,

Sloswicke Drive, Retford

DN22 7WQ

UNITED KINGDOM

TEL: +44 (0)1777 710100

EMAIL: sales@paintman.co.uk

- · Further information obtainable from: www.paintman.co.uk
- · 1.4 Emergency telephone number: +44 (0)1777 710100 (business hours)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms









GHS02

GHS07

GHS08

GHS(

- · Signal word Danger
- · Hazard-determining components of labelling:

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) cobalt bis(2-ethylhexanoate) phthalic anhydride

· Hazard statements

Hazara statements
H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H372 Causes damage to organs through prolonged or repeated exposure.

(Contd. on page 2)

(Contd. of page 1)

Safety data sheet according to UK REACH

Version number: 1.03 Printing date 08.07.2025 Revision: 08.07.2025

Trade name: Red Oxide Synthetic Primer

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101

If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

EC number: 919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2%	>10-<25%
	aromatics	
	♦ Flam. Liq. 3, H226	
	♦ Asp. Tox. 1, H304	
	♦ STOT SE 3, H336	
EC number: 919-446-0	Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics,	>10-≤25%
Reg.nr.: 01-2119458049-33-xxxx	aromatics (2-25%)	
	Flam. Liq. 3, H226	
	♦ STOT RÊ 1, H372; Asp. Tox. 1, H304	
	Aquatic Chronic 2, H411	
	♦ STOT SE 3, H336	
CAS: 7779-90-0	trizinc bis(orthophosphate)	>2.5- <u>≤</u> 10%
EINECS: 231-944-3	🕸 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
Reg.nr.: 01-2119485044-40-0000		
EC number: 918-668-5	Hydrocarbons, C9, aromatics	>2.5-≤10%
Reg.nr.: 01-2119455851-35-xxxx	Flam. Liq. 3, H226	
	♦ Asp. Tox. 1, H304	
	Aquatic Chronic 2, H411	
	♦ STOT SE 3, H335-H336	
CAS: 97952-68-6	Quaternary ammonium compounds, benzylbis (hydrogenated	>1-≤2.5%
EC number: 308-361-9	tallow alkyl)methyl,salts with montmorillonite	
	♦ STOT RE 2, H373	
CAS: 136-52-7	cobalt bis(2-ethylhexanoate)	≤1%
EINECS: 205-250-6	♦ Repr. 1A, H360Fd	
Reg.nr.: 01-2119524678-29	Aquatic Acute 1, H400	
	Eye Irrit. 2, H319; Skin Sens. 1A, H317	
	Aquatic Chronic 3, H412	
CAS: 85-44-9	phthalic anhydride	≤1%
EINECS: 201-607-5	& Resp. Sens. 1, H334	
Reg.nr.: 01-2119457017-41	Eye Dam. 1, H318	
	Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1,	
	H317; STOT SE 3, H335	

(Contd. on page 3)

Trade name: Red Oxide Synthetic Primer

(Contd. of page 2)

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing.

- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing:

Do not induce vomiting; call for medical help immediately and show safety datasheet or label.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/extraction at the workplace.

Prevent formation of aerosols.

(Contd. on page 4)

Printing date 08.07.2025 Version number: 1.03 Revision: 08.07.2025

Trade name: Red Oxide Synthetic Primer

(Contd. of page 3)

Hygiene measures:

Wash hands before breaks and at the end of workday.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage.
- · Requirements to be met by storerooms and receptacles:

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risk of fires, all contaminated materials should be [stored in purpose-built containers or in metal containers with tight-fitting self-closing lids.] or [laid out flat in a single layer to dry] or [placed in a metal container soaked with water] or [washed out well with warm soapy water before disposal.] Contaminated materials should be removed from the workplace at the end of each working day and stored outside.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed and in a well-ventilated place.

Keep away from heat.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see section 7.
- · Ingredients with limit values that require monitoring at the workplace:

Hydrocarbons, C9, aromatics

OEL Long-term value: 100 mg/m³

136-52-7 cobalt bis(2-ethylhexanoate)

WEL Long-term value: 0.1 mg/m³

as Co; Carc, Sen

85-44-9 phthalic anhydride

WEL Short-term value: 12 mg/m³
Long-term value: 4 mg/m³

· PNECs

CAS No. 1330-20-7 Xylene mixed isomers

- Fresh water; 0.327 mg/l
- Marine water; 0.327 mg/l
- Intermittent release; 0.327 mg/l
- STP; 6.58 mg/l
- Sediment (Freshwater); 12.46 mg/kg
- Sediment (Marinewater); 12.46 mg/kg
- Soil; 2.31 mg/kg
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Respiratory protection: When spraying the product, use a respiratory protective device.

(Contd. on page 5)

(Contd. of page 4)

Safety data sheet according to UK REACH

Trade name: Red Oxide Synthetic Primer

· Protection of hands:

When skin exposure may occur, advice should be sought from the glove supplier on appropriate types and usage times for this product.



Protective gloves

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid Colour: Red

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. **Initial boiling point and boiling range:** 139 °C

· Flash point: 38 °C

· Flammability Flammable.

· Auto-ignition temperature: >200 °C

• **Decomposition temperature:** Not determined.

• Ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

 Lower:
 0.6 Vol %

 Upper:
 7 Vol %

· Vapour pressure: Not determined.

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

· Evaporation rate Not determined.

· Solubility in / Miscibility with

water: NOT MISCIBLE

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic at 20 °C: Sinematic:330 mPas
Not determined.

(Contd. on page 6)

Trade name: Red Oxide Synthetic Primer

· Solvent content: Organic solvents:	30.7 %	page 3
Solids content:	69.9 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable under normal conditions
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

No dangerous decomposition products when stored and handled correctly

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- $\cdot \textbf{STOT-single exposure} \ \textit{Based on available data}, \ \textit{the classification criteria are not met}.$
- · STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

Acute Fish toxicity

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

LC50 9.22 mg/l

Species: Oncorhynchus mykiss (rainbow trout)

Exposure duration: 96 h

Acute toxicity for daphnia

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

EC50 6.14 mg/l

Species: Daphnia magna (Water flea)

Exposure duration: 48 h

Acute toxicity for algae

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

ErC50 2.9 mg/l

(Contd. on page 7)

(Contd. of page 6)

Safety data sheet according to UK REACH

Trade name: Red Oxide Synthetic Primer

Species: Pseudokirchneriella subcapitata (green algae)

Exposure duration: 72 h

Acute bacterial toxicity

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

EC50 1 - 10 mg/l

Ecotoxicology Assessment

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

Chronic aquatic toxicity: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Data based on the safety data sheet (SDS) by the supplier.

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, IMDG, IATA

UN1263

· 14.2 UN proper shipping name

 $\cdot ADR$

1263 PAINT, ENVIRONMENTALLY HAZARDOUS

· **IMDG** PAINT, MARINE POLLUTANT

· IATA PAINT

- · 14.3 Transport hazard class(es)
- · ADR, IMDG



· Class 3 Flammable liquids.

(Contd. on page 8)

 Printing date 08.07.2025
 Version number: 1.03
 Revision: 08.07.2025

Trade name: Red Oxide Synthetic Primer

	(Contd. of page
Label	3
IATA	
<u>~</u>	
3	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	no
a	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	<i>F-E,<u>S-E</u></i>
Stowage Category	A
14.7 Transport in bulk according to Annex II of	pf
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
Towns and a set a set as a set.	Maximum net quantity per outer packaging: 1000 ml
Transport category Tunnel restriction code	3 D/E
	DIE
IMDG	£1
Limited quantities (LQ)	5L Code: E1
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALL
•	HAZARDOUS

SECTION 15: Regulatory information

 $\cdot\,15.1\ Safety,\ health\ and\ environmental\ regulations/legislation\ specific\ for\ the\ substance\ or\ mixture$

	· MAK (German Maximum Workplace Concentration)			
Ī	100-41-4 ethylbenzene	3A		
	· Poisons Act			
	· Regulated explosives precursors			
	None of the ingredients is listed.			
	· Regulated poisons			
	None of the ingredients is listed.			
	· Reportable explosives precursors			
	None of the ingredients is listed.			

(Contd. on page 9)

Trade name: Red Oxide Synthetic Primer

(Contd. of page 8)

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Technical instructions (air):

Class	Share in %
Ι	0.1
NK	30.7

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Full text of H-Statements referred to under sections 2 and 3:

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H360Fd May damage fertility. Suspected of damaging the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- *H400 Very toxic to aquatic life.*
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

· Department issuing SDS: Product safety department: LABORATORY

- · Contact: Health & Safety Officer
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PNEC: Predicted No-Effect Concentration (UK REACH)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

(Contd. on page 10)

Trade name: Red Oxide Synthetic Primer

Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation — Category 2 Resp. Sens. 1: Respiratory sensitisation — Category 1 Skin Sens. 1: Skin sensitisation — Category 1 Skin Sens. 1A: Skin sensitisation — Category 1A Repr. 1A: Reproductive toxicity — Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* * Data compared to the previous version altered.

GB